



## Heating Coils Fax Inquiry

Please send the inquiry for your **AdcaTherm** steam to water heating coil ( for existing vessels) with the following parameters:

STORAGE HOT WATER VESSELS – CLOSED TYPE			
	TUBE SIDE		VESSEL SIDE
FLUID	SATURATED STEAM		WATER
OPERATING PRESSURE	bar		bar
INITIAL TEMPERATURE	-----		° C
FINAL TEMPERATURE	-----		° C
VESSEL CAPACITY	-----		Kg or m3
RECOVERY PERIOD (In minutes)	‘		
HEAT EXCHANGED (Option)	KW or		Kcal/h
VESSEL TYPE (Please select)	HORIZONTAL	<input type="checkbox"/>	VERTICAL
AVAILABLE DIMENSIONS (Send a sketch)	Straight length	mm	Diameter mm

Remarks : A coil in a cylindrical vertical vessel should be as close to but not exceeding the diameter of the vessel as possible. A coil in a horizontal vessel is typically approximately 2/3 the length of the vessel

### SEMI – INSTANTANEOUS HOT WATER HEATER

**If the vessel is also operating as semi-instantaneous hot water heater, please confirm :**

HOT WATER CONSUMPTION	m3
INCOMING COLD WATER TEMPERATURE	° C
DESIRED HOT WATER TEMPERATURE	° C
LENGTH OF TIME (IN MINUTES)	‘

### INSTANTANEOUS HOT WATER HEATER

**If the vessel is also operating as instantaneous hot water heater, please confirm:**

HOT WATER CONSUMPTION	m3/h
INCOMING COLD WATER TEMPERATURE	° C
DESIRED HOT WATER TEMPERATURE	° C

Remarks: If the instantaneous hot water consumption is greater than three times the storage capacity of the vessel, then the heating coil may be baffled to allow for an integral pump to force circulate water over the heating coil.

We may also recommend the vessel capacity. In this case please supply all the consumption details such as quantity of water and temperatures.

Your company name:	
Contact :	
Address :	
Country :	
Tel.:	Fax.:
E-mail:	Web-page:

Valsteam ADCA Eng. SA – Portugal Tel.: ++351 244 860 240 Fax.: ++351 244 861 770 E-mail: adca@valsteam.pt